

**THE NEXT
GENERATION**
15 YEARS GUARANTEE*
check-floors.com

CHECK ✓
one

Standard Collection
with integrated underlay

Product information

Guarantee	15 years*
Clicksystem	Loc-Click
Chamfer	bevelled edge (plank) 4V-groove (wide plank)
Sealing	UV varnish
Wear layer	0.3 mm
Utilisation class	33 (plank) 34 (wide plank)

Technical data

Dimension		1220 x 182 x 5 mm
Packing unit (PU)	Plank	10 Planks = 2.220 sqm
Pallet size		44 PU = 97.70 sqm
Dimension		1220 x 228 x 5 mm
Packing unit (PU)	Wide Plank	8 Planks = 2.225 sqm
Pallet size		39 PU = 86.79 sqm

Test results

Lightfast	ISO 105-B02	6
Dimensional stability	ISO 23999	✓
Fire behavior	EN 13501-1	Bfl, s1
Straightness and squareness	ISO 24342	0.03 mm / 0.04 mm
Resistance to staining	EN ISO 26987	✓
Residual indentation	ISO 24343	0.02 mm
Slip resistance	EN 13893	DS
Anti-Slip property	DIN 51130	R10
Thermal Resistance	EN12667	0.061 m ² K/W
Underfloor heating	EN12667	Suitable for hot water, max. 27 degrees
Formaldehyde class	EN 717-1	E1
Chair castor suitability	ISO 4918	no damage
Impact sound reduction	ISO 10140-1; ISO 717-2	19 dB

* according to guarantee conditions

All specified values are standard values.
Production-related fluctuations can not be ruled out.

